

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A toeboard for a raised working platform, said toeboard comprising
an elongate body member with connectors at opposite ends thereof,
each connector extending inline with and beyond said elongate body member with two adjacent fingers at the free end thereof and extending in a manner to intersect with a longitudinal axis of said elongate member,
said connectors at opposite ends of said elongate body having an opposite orientation with the fingers of one connector orientated in a first direction and the fingers of the opposite connector orientated 180 degrees to said first direction.
2. A toeboard as claimed in claim 1 wherein an outermost finger of said two fingers is offset relative to the other finger to locate it to one side of said other finger.
3. A toeboard as claimed in claim 1 wherein said elongate body is made of a metal and is generally "L" shaped in cross section defined by an upright portion and a foot portion.
4. A toeboard as claimed in claim 3 wherein each connector is a metal plate secured to said upright portion on the side thereof above said foot portion.
5. A toeboard as claimed in claim 5 wherein the fingers of each connector terminate within a height dimension of said upright portion.
6. A toeboard as claimed in claim 5 wherein the outermost finger is shorter than the other finger.

7. A toeboard as claimed in claim 6 wherein said elongate body has a series of securing holes spaced in the length of said elongate body for securing of said toeboard during lifting thereof.

8. In a scaffolding system having at least one raised working platform with a toeboard system about a perimeter of said working platform, said toeboard system comprising a series of connected toeboards;

each toeboard comprising

an elongate body member with connectors at opposite ends thereof,

each connector extending inline with and beyond said elongate body member with two adjacent fingers at the free end thereof and extending in a manner to intersect with a longitudinal axis of said elongate member,

said connectors at opposite ends of said elongate body having an opposite orientation with the fingers of one connector orientated in a first direction and the fingers of the opposite connector orientated in a direction 180 degrees to said first direction;

each toeboard being connected to adjacent toeboards due to engagement of connectors of adjacent toeboards.

9. In a scaffolding system as claimed in claim 8 wherein said toeboards connect one to another such that the cooperating connectors of the toeboard are interengaged and the interengaged connectors are positioned in a gap between a wedge member and an upright support member of said scaffolding system.

10. In a scaffolding system as claimed in claim 9 wherein some of said toeboards are connected in an end to end manner using outermost fingers of the connectors of the respective toeboards, and some of said toeboards are

connected at an angle using inner fingers of the connectors of the respective toeboards.